





# La Frange Polymorphique de l'Internet


Laurent Toutain, Pascal Thubert


June 26, 2013













# Common Language Interconnection



Common Language  
Interconnection




Ossification





# ARESA2 Project


- ANR Verso 2009 project
- Urban Wireless Sensor Networks
  - AMI, Smart Grid, M2M...
- One of the challenges: IPv6
  - Mesh network.
  - Minimize code footprint, minimize energy consumption.














**SLLAO**: Source Link-layer Address, **PIO**: Prefix Information, **6CO**: 6LoWPAN Context, **ABRO**: Authoritative Border Router




**SLLAO**: Source Link-layer Address, **PIO**: Prefix Information, **6CO**: 6LoWPAN Context, **ABRO**: Authoritative Border Router




**SLLAO**: Source Link-layer Address, **PIO**: Prefix Information, **6CO**: 6LoWPAN Context, **ABRO**: Authoritative Border Router








**DAR:** Duplicate Address Request




**DAC:** Duplicate Address Confirmation













**RPL:** Routing Protocol for Low power and lossy networks, **DIS:** DODAG (Destination Oriented Directed Acyclic Graph) Information Solicitation














**RPL:** Routing Protocol for Low power and lossy networks, **DIS:** DODAG (Destination Oriented Directed Acyclic Graph) Information Solicitation











GSE - An Alternate Addressing Architecture for IPv6  
<draft-ietf-ipngwg-gseaddr-00.txt>

The 16 byte IPv6 address is split into 3 pieces:

```
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
+-----+-----+-----+-----+-----+
| Routing Goop | STP | End System Designator |
+-----+-----+-----+-----+
          6+ bytes      2 bytes      8 bytes
```

Routing Goop signifies where the Site attaches to the Global Internet. The Site Topology Partition (STP) is Site-private "LAN segment" information. The End System Designator (ESD) specifies an interface on an end-system.

Rewriting IPv6 addresses by Site Border Routers is by far the most controversial, but also most critical part of this proposal. To control the complexity of routing information which must be managed within a Site and to isolate end systems and interior routers from external topology changes, the RG of some addresses is modified by Site Border Routers. Packets exiting a site have the RG for the Site egress point inserted into source addresses, while packets entering a Site have the RG in all destination addresses replaced with a canonical prefix signifying "within this Site" (the "Site-local prefix").

GSE - An Alternate Addressing Architecture for IPv6  
<draft-ietf-ipngwg-gseaddr-00.txt>

In 1997: cannot guaranty unique ESD (IID) for global Internet

The 16 byte IPv6 address is split into 3 pieces:

```
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
+-----+-----+-----+
| Routing Goop | STP | End System Designator |
+-----+-----+-----+
      6+ bytes      2 bytes      8 bytes
```

Routing Goop signifies where the Site attaches to the Global Internet. The Site Topology Partition (STP) is Site-private "LAN segment" information. The End System Designator (ESD) specifies an interface on an end-system.

Rewriting IPv6 addresses by Site Border Routers is by far the most controversial, but also most critical part of this proposal. To control the complexity of routing information which must be managed within a Site and to isolate end systems and interior routers from external topology changes, the RG of some addresses is modified by Site Border Routers. Packets exiting a site have the RG for the Site egress point inserted into source addresses, while packets entering a Site have the RG in all destination addresses replaced with a canonical prefix signifying "within this Site" (the "Site-local prefix").

GSE - An Alternate Addressing Architecture for IPv6  
<draft-ietf-ipngwg-gseaddr-00.txt>

In 1997: cannot guaranty unique ESD (IID) for global Internet

The 16 byte IPv6 address is split into 3 pieces:


```
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
+-----+-----+-----+
| Routing Goop | STP | End System Designator |
+-----+-----+-----+
      6+ bytes      2 bytes      8 bytes
```


Routing Goop signifies where the Site attaches to the Global Internet. The Site Topology Partition (STP) is Site-private "LAN segment" information. The End System Designator (ESD) specifies an interface on an end-system.


Rewriting IPv6 addresses by Site Border Routers is by far the most controversial, but also most critical, aspect of routing informati

Possible with LoWPAN Network: IID is unique in this area

to isolate end systems and interior routers from external topology changes, the RG of some addresses is modified by Site Border Routers. Packets exiting a site have the RG for the Site egress point inserted into source addresses, while packets entering a Site have the RG in all destination addresses replaced with a canonical prefix signifying "within this Site" (the "Site-local prefix").







## Ethernet



## IPv6

## Ethernet




## IPv6



## Ethernet



## IPv6




Minimum Information

## Ethernet



## IPv6




Minimum Information

May Evolve though other standards:

- IEEE 802.11, IEEE 802.16, ...
- MACinMAC

## Ethernet




### Minimum Information

May Evolve though other standards:


- IEEE 802.11, IEEE 802.16, ...
- MACinMAC


## IPv6





Fixed header, no evolution.

- Extensions are designed for this !  
⇒ Wrong design ?
- Internet is no more homogeneous











# 6LoWPAN: Route Over

Breaking the Hourglass




# 6LoWPAN: Route Over

Breaking the Hourglass




# 6LoWPAN: Route Over

Breaking the Hourglass




# 6LoWPAN: Route Over

Breaking the Hourglass




# 6LoWPAN: Route Over

Breaking the Hourglass




# 6LoWPAN: Route Over

Breaking the Hourglass




# 6LoWPAN: Route Over

Breaking the Hourglass




# 6LoWPAN: Route Over

Breaking the Hourglass





# 6LoWPAN: Route Over

Breaking the Hourglass











RFC 2460: With one exception, extension headers are not examined or processed by any node along a packet's delivery path , until the packet reaches the node (or each of the set of nodes, in the case of multicast) identified in the Destination Address field of the IPv6 header.




# Upward traffic: DoDAG


Breaking the Hourglass





# Upward traffic: DoDAG



Breaking the Hourglass













# DNS: CoAP Mode

Breaking the Hourglass








Heterogeneous wireless sensor network

see

<https://github.com/telecombretagne/Arduino-IPv6Stack>







Deterministic Communications ?

